

# Product Data Sheet

No. 11601 - 05/16

## ROOF ACCESSORY & TRIM PAINT

AEROSOL VOC/CARB MIR: Flat <60% / ≤ 1.2

### PRODUCT NUMBERS:

1601 - CEDAR	1612 - DARK BROWN
1603 - RUSTIC BROWN	1613 - TERRA COTTA
1604 - DRIFTWOOD	1616 - ADOBE
1606 - BIRCHWOOD	1625 - BONE WHITE
1608 - SLATE GRAY	1626 - SIERRA TAN
1609 - RUSTIC BLACK	

### I. GENERAL DESCRIPTION

**Features:** This high quality lacquer coating is formulated for exterior use on roofing accessories. This product is available in 11 of the most commonly used OEM colors. Durable color fastness, good hide and coverage. This product provides long term protection against rust, corrosion, and discoloration on metal and other roofing accessory materials. Easy application, great color selection, superior durability, while extending the life of all roofing accessory materials.

**Benefits:** Aervoe Roof Accessory & Trim Paint is a fast-drying industrial grade lacquer. Excellent adhesion to all metal, plastic, vinyl, wood and masonry surfaces. Provides a professional coating on surfaces where brush application may be difficult. The finish dries to the touch in minutes and yields a full cure in 24 hours. Exceptional resistance to water, sun (UV rays), snow, and other harsh environmental conditions.

**Applications:** Use on metal, plastic, vinyl, wood, concrete, and masonry. Specifically designed for roof vents, flashing, valleys, and other metal and/or plastic roof accessories.

**Directions:** For maximum adhesion, surface must be clean, dry and free of grease, rust, scale or any other loose particles. Over galvanized steel a primer is not recommended. Product should be used at temperatures between 60° and 85° (16° and 29°C) for best results. Shake can well for at least one minute after agitator ball begins to rattle. Shake can intermittently during use. Hold can 8 to 10 inches from surface and press spray head firmly. Apply with steady, even strokes; two light coats are better than one heavy coat. Clear spray tip after each use by turning can upside down and spraying for 2 seconds.

**Limitations:** Please refer to the Safety Data Sheets for specific information on material hazards, etc. Please check all plastic surfaces for adhesion and compatibility before each use.

#### Packaging:

Aerosol:	Cans (211x604)	12 oz. net wt. (340 g)	14.6 fl. oz. (432 ml)
	Case (12/case):	14 lbs. (6.35 kg)	0.47 CF (0.013 CM)

---

## II. CHARACTERISTICS & PROPERTIES (Average for all colors)

---

### Specifications:

Complies with CARB Flat and Non-flat MIR regulations for aerosol coatings.

### Appearance:

Gloss at 60° ..... Flat <5  
Class ..... Flat

### Coverage:

Theoretical—at 1 mil dry ..... 17 sq. ft./can.

### Drying Schedule: (At 77°F [25°C], 50% Humidity at 1 mil, dry)

To touch ..... 5 min.  
To handle ..... 15 min.  
Full cure ..... 24 hrs.  
To recoat ..... Any time

### Performance and Chemical Properties:

Weight per gallon ..... 5.22 lbs.  
Specific gravity ..... 0.62  
Flammability: Label marking ..... Extremely flammable  
Flash point ..... <0°F (-18°C)  
Operating temperature range ..... 55° to 95°F (13° to 35°C)  
Percent solids by weight ..... 21%  
Percent solids by volume ..... 9 %  
Percent pigment by volume ..... 3 %  
CARB MIR Flat ..... <1.2  
Volatile Organic Compound limit ..... <60%  
Exterior durability ..... Excellent  
Temperature resistance ..... 300°F (149°C)  
Color fastness ..... Excellent  
Adhesion ..... Excellent over properly prepared surface  
Mineral spirits resistance ..... Excellent  
Gasoline resistance ..... Poor  
Motor oil resistance ..... Excellent  
Pencil hardness ..... HB

### Base Materials:

Resin system ..... Acrylic  
Solvents (top two) ..... Acetone, Methyl Acetate  
Propellant system ..... Hydrocarbon

---

## III. SHIPPING, STORAGE AND HEALTH

---

UN number ..... UN1950  
Proper Shipping Description ..... Aerosols  
Hazard Class ..... 2.1  
Packing Group ..... N/A  
Limited Quantity ..... Yes  
Warehouse storage level number ..... NFPA 30B Level 2  
Storage temperature ..... 32° to 120°F (0° to 49°C)  
Shelf life ..... 1 to 2 years  
HMIS ratings  
Health ..... 2  
Fire ..... 4  
Reactivity ..... 1

---

## IV. MISCELLANEOUS

---

Contains no Ozone Depleting Substances (O.D.S.)

---

## V. WARRANTY

---

The statements made herein, on labels, product bulletins or by any of our employees or agents concerning this material are given for information only. Any liability whatsoever of Aervoe Industries, Inc. to the user of the product, is limited to replacement of the product or purchase price refunded.