

Product Data Sheet

No. 14750 - 07/15

GREEN-OUT COVER COATING

Aerosol VOC <66%; CARB MIR \leq 1.20 ground traffic/marketing coatings

PRODUCT NUMBERS: 4750

Product number plus letter designation is as follows:

G = 1 one-gallon jug

I. GENERAL DESCRIPTION

Description: Green-Out Cover Coating is a highly pigmented dye formulated to safely cover dead grass and rejuvenate it back to health. Lasts 6 to 8 weeks and is a low cost answer to off-season "green." Dries in 5 minutes and is easy to clean up.

Benefits: Covers dead grass to create the look of healthy grass, even in the dormant season. Helps to rejuvenate damaged grass back to health.

Uses: Use on golf courses, athletic fields, home or office lawns, and any other grass damaged by severe weather, animal urination, or insect damage. Great for foreclosed home beautification. Use the aerosol as a quick fix for small spots. For larger area coverage, use the gallon container with any spray applicator. Product can be used at full strength or diluted with water to blend with color of existing healthy grass.

Application: Aerosol: Shake can vigorously for at least one minute after rattle of agitator ball is heard and intermittently during use. Use at temperatures between 40° and 80°F (5° and 27°C). Invert the can and activate by hand, pushing the spray tip to the side, or use the Aervoe #745 Striping Stick. To prepare can for storage, remove from applicator, turn can upright and spray for 2 to 3 seconds to clear paint from the valve. **Bulk:** Shake gallon container well. Pour contents into any spray applicator or standard garden sprayer. Use full strength, or dilute with water to blend with existing grass color. For color and coverage equal to the aerosol application, mix 8 parts water to 1 part Green-Out. Do not freeze.

Limitations: Refer to Safety Data Sheet for specific information on material hazards.

Packaging:

Aerosol:	Cans (211x713)	18 net wt. (510 g)	14.8 fl. oz. (437 ml)
	Case (12/case):	19 lbs. (8.6 kg)	0.55 CF (0.016 CM)
Bulk:	Case 1 gallon	12 lbs. (5.4 kg)	0.25 CF (0.004 CM)

II. CHARACTERISTICS & PROPERTIES

Specifications: Aerosol complies with CARB MIR regulations

Appearance:

	Aerosol	Bulk
Gloss at 60°	N/A	N/A
Class	N/A	N/A

Coverage:

Theoretical—at 1/2 mil dry.....	60 sq. ft./can	1 gallon thinned = 2000 sq. ft.
Practical—at 1 mil dry.....	30 sq/ ft./can	1 gallon thinned = 1000 sq. ft.

Drying Schedule: (At 77°F [25°C], 50% Humidity at 1 mil, dry)

To touch.....	30 min.	30 min.
To handle.....	60 min.	60 min.
Full cure	8 hrs.	8 hrs.
To recoat	Anytime	Anytime

Performance and Chemical Properties:

Weight per gallon	7.7 lbs.	9.62
Specific gravity	0.92	1.1
Viscosity	N/A	N/A
Flammability: Label marking	Caution Contents Under Pressure	Non Flammable
Flash point.....	<0°F (-18°C)	N/A
Operating temperature range.....	50° to 80°F (10° to 27°C).....	50° to 80°F (10° to 27°C)
Percent solids by weight	32%.....	40.2%
Percent solids by volume	15%.....	26%
Percent pigment by volume.....	1%.....	8%
Volatile Organic Compound level.....	<66%	<66%
CARB MIR<	1.20% Ground Traffic.....	N/A
Interior durability.....	Good	Good
Exterior durability	Good	Good
Temperature resistance.....	N/A	N/A
Color fastness	Excellent	Excellent
Adhesion	N/A	N/A
Mineral Spirits resistance.....	N/A	N/A
Gasoline resistance.....	N/A	N/A
Motor oil resistance.....	N/A	N/A
Food contact rating.....	N/A	N/A

Base Materials:

Resin system.....	Polyvinyl Acetate.....	Polyvinyl Acetate
Solvents (top two)	Water	Water
Propellant system.....	Dimethyl Ether	N/A

III. SHIPPING, STORAGE AND HEALTH

	Aerosol	Bulk
UN number.....	UN1950.....	N/A
Proper Shipping Description	Aerosols.....	Non-regulated material
Hazard Class.....	2.1	N/A
Packing Group	N/A	N/A
Limited Quantity	Yes	N/A
Warehouse storage level number	NFPA 30B Level 1.....	N/A
Storage temperature	45° to 120°F (7° to 49°C).....	45° to 120°F (7° to 49°C)
Shelf life	1 year.....	1 year
HMIS ratings		
Health.....	1	1
Fire	1	1
Reactivity.....	0	0

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year warranty to the original registered owner on all products from date of purchase. User returns, exchanges and defective refunds must be made with the original place of purchase. Because Aervoe cannot control Buyer's handling or use of product, Aervoe makes no warranty expressed or implied when not used or stored in accordance with directions. Aervoe shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement or repair of product or credit of purchase.