# **Product Data Sheet**

No. 23460 - 3/13

# PAINTABLE MOLD RELEASE

PRODUCT NUMBERS: 3460 - 13-OZ. AEROSOL

#### I. GENERAL DESCRIPTION

**Description:** This paintable mold release will not interfere with parts to be painted, adhesive bonded, heat sealed, heat stamped, or laminated. Non-chlorinated formula.

**Benefits:** Withstands temperatures up to 500°F. This product can be painted with all types of solvent-based paint, enamels, and lacquers.

**Application:** Use as mold release for acrylics, melamines, phenolics, polyesters, polyethylene, polypropylene, PVC, nylon, polystyrenes, polycarbonates, and rubber.

**Directions:** Hold can 6 to 8 inches from surface. Use smooth motion to spray on even coat. For best results, can should be at room temperature 70° F (21° C). For post molding decorating, or painting, no special cleaning is necessary.

**Limitations:** Please refer to the Safety Data Sheet for specific information on material hazards, etc.

Packaging:

Cans - (211 x 713) 13 oz. net wt.. (369 grams) 19.5 fl. oz. (577 ml) Case - 12 cans/case 15 lbs. (6.8 kg) .55 CF (.016 CM)









# **II. CHARACTERISTICS & PROPERTIES**

### Specifications:

None

#### Appearance:

Non-foaming liquid

#### Color:

Clear, transparent

#### Odor:

Hydrocarbon

# Dry Schedule:

<1 minute

#### **Performance and Chemical Properties:**

criorinance and offernical rioperties.	
Weight per gallon	5.4 lbs
Specific gravity	0.65
Viscosity	N/A
Flammability: Label marking	
Flash point	<del>-</del>
Operating temperature range	
Active ingrediants by weight	
Volatile Organic Compound Level	
Dielectric strength	
Lubricity (FALEX FLC Test)	
Penetrating ability	
Corrosion protection	
Food contact rating	

Propellent: Hydrocarbon

# III. SHIPPING, STORAGE AND HEALTH

UN number	
Proper Shipping Description	Aerosols
Hazard Class	2.1
Packing Group	N/A
Limited Quantity	Yes
Warehouse storage level number	NFPA 30B Level 2
Storage temperature	32° to 120°F (0° to 4
Shelf life	1 to 5 years
HMIS ratings	
Health	1
Fire	3
Reactivity	0

# IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

## V. WARRANTY

120°F (0° to 49°C)

1-year performance warranty on all products from date of purchase. Report to home office or local Aervoe representative for examination. Because Seller cannot control Buyer's handling or use of product, Seller makes no warranty expressed or implied when not used or stored in accordance with directions. Seller shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement of product or credit of purchase. No. 23460 - 03/13