# Aervoe APC-961 Grease Free Lube / Film - Bulk



The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know.

This MSDS covers the following Aervoe bulk product.

PRODUCT NAME: APC-961 Grease Free Lube / Film

#### SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Aervoe Industries Inc.

ADDRESS: 1198 Mark Circle, Gardnerville, NV 89410

**INFORMATION PHONE:** 775-782-0100

**EMERGENCY PHONE:** 1-800-424-9300

**DATE REVISED: 10-03-08** 

**REASON REVISED: Updated** 

## SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION **OCCUPATIONAL EXPOSURE LIMITS**

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE	
Aliphatic Petroleum Distillates (CAS 64742-47-8) 30 - 60		N / AV	N / AV		N / AV	N / AV	

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

SPECIFIC GRAVITY (H20=1): 0.9 COEFFICIENT OF WATER/OIL DIST: N / AV

**BOILING POINT:** 370° F (188° C) ODOR THRESHOLD: N / AV VAPOR DENSITY: Heavier than air **SOLUBILITY IN WATER: Negligible EVAPORATION RATE:** Slower than n-Butyl Acetate APPEARANCE AND ODOR: Clear light amber with sweetish odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT:** > 230° F (110° C) METHOD USED: PMCC FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 1.4% UPPER: 8.1%

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Water Spray

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool containers exposed to heat or fire to prevent pressure build up.

Self-contained breathing apparatus should be used if product is involved in fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may rupture due to pressure build up from extreme heat or fire.

SENSITIVITY TO IMPACT: Do not puncture SENSITIVITY TO STATIC DISCHARGE: N / AV

## **SECTION V - REACTIVITY DATA**

STABILITY: Stable CONDITIONS TO AVOID: Open flames, sparks, electrical arcs.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION: Will not occur

## SECTION VI - HEALTH HAZARD DATA

INHALATION: Respiratory tract irritant. May cause dizziness, light-headedness and / or headaches.

**SKIN CONTACT:** Prolonged or repeated contact may cause irritation and dermatitis.

EYE CONTACT: Painful with slight to moderate irritation.

SKIN ABSORPTION: Not likely to be absorbed in toxic amounts under normal use. INGESTION: Not likely in normal use but swallowing large amounts may be harmful.

CARCINOGENICITY: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.

TERATOGENICITY: Not established **MUTAGENICITY:** Not established MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE: Not established

EMERGENCY AND FIRST AID PROCEDURES: INHALATION - Remove from exposure, seek medical attention if signs/symptoms persist.

SKIN - Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.

EYES - Flush immediately with water for 15 minutes, seek medical attention if irritation persists.

INGESTION - Do NOT induce vomiting, drink plenty of water, seek medical attention if irritation persists.

#### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120° F (49°C). Do not store or use near heat, sparks or flame.

OTHER PRECAUTIONS: Do not smoke while using this product.

## SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator.

For concentrations above the TLV (as defined in Section II), use a positive air supplied respirator. VENTILATION: General ventilation to maintain exposure limits below TLV's as defined in Section II.

PROTECTIVE GLOVES: Chemical resistant gloves such as Neoprene or Nitrile rubber.

EYE PROTECTION: Safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None

WORK / HYGIENIC PRACTICES: Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

#### **SECTION IX - DISCLAIMER**

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.

<sup>\*\*\*</sup>No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.\*\*\* **NOTE:** N / AP = Not Applicable N / AV = Not Available